



Submittal: NPSHZ0808ZWH



$\mathsf{STRONG\text{-}POINT}^{ ext{@}}$ SLOTTED INDENTED HEX WASHER HEAD PAINTED WHITE, ZINC PLATED

Size	Part#	Case Qty.	Description
8 x 1/2	NW808	15M	Slotted Indented Hex Washer Head Painted White, Zinc Plated
8 x 3/4	NW812	10M	Slotted Indented Hex Washer Head Painted White, Zinc Plated
8 x 1-1/2	NW824	5M	Slotted Indented Hex Washer Head Painted White, Zinc Plated
8 x 2	NW832	3M	Slotted Indented Hex Washer Head Painted White, Zinc Plated
Application:	Attaches light gauge sheet metal to sheet metal or wood.		
Specifications:	 Meets ASTM¹ A 510 for carbon steel manufacturing Meets ASTM B 633 for electrodeposited zinc coatings Meets ASTM F1941 for corrosion resistance 		
Features:	 Multipurpose sheet metal screw for light to medium gauge applications 22° point pierces light gauge metal Twin fast thread design creates faster installation speeds 		
Installation:	A 1/4" hex nut setter or 1/4" drive socket with torque limiting nose piece set at a minimum of 1400 RPM drive speed recommended.		

Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.