



## **EXTERIOR SCREWS**

Use when installing wood decking and fencing.



Grip-Rite® exterior screws feature star drive heads to reduce cam outs when driving into your outdoor project. Type 17 point tip reduces the need to pre-drill and helps keep the material from splitting. Coarse threading pulls the substrates together for a solid, tight connection.

For use with treated and untreated lumber.

- Head Type Bugle Head
- Drive Type Star Drive T-25, Star Drive T-30
- Thread Type Coarse Thread
- Finish PrimeGuard Plus® with Lifetime Coating
- Point Type 17 Point
- Available Colors Black, Gold, Gray, Green, Red, Tan and White



GAUGE	LENGTH	STAR DRIVE	TPI	HEAD DIAMETER
#8	1-1/4"	T-25	8	8.00-9.00MM
#8	1-5/8"	T-25	8	8.00-9.00MM
#8	2"	T-25	8	8.00-9.00MM
#9	2"	T-25	8	8.00-9.00MM
#9	2-1/2"	T-25	8	8.00-9.00MM
#9	3"	T-25	8	8.00-9.00MM
#10	3-1/2"	T-25	8	8.50-9.50MM
#10	4"	T-25	8	8.50-9.50MM
#1/4	5"	T-30	7	10.20-12.20MM
#1/4	6"	T-30	7	10.20-12.20MM

ALL PRIMESOURCE® FASTENERS ARE MANUFACTURED IN AN ISO 9002 AND ISO 14001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE® PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.





A PrimeSource® Brands Company

PSB PRIMESOURCE®
BRANDS

Contact your PrimeSource Building Products representative to order today. 800-676-7777 | primesourcebp.com