



Submittal: DSSTLT7ZY1056



STRONG-POINT® STAR DRIVE FLAT HEAD w/NIBS, TYPE '17', ZINC YELLOW

Size	Part#	Case Qty.	Description						
10 x 3-1/2	XT1031Y	1M	Star Drive Flat Head w/Nibs, Type '17', Zinc Yellow						
10 x 4	XT1040Y	.8M	Star Drive Flat Head w/Nibs, Type '17', Zinc Yellow						
Application:	For interior or outdoor applications. Attaches wood to wood.								
Specifications:	 Meets ASTM¹ A 510 for carbon steel manufacturing Product meets ASTM B-117 for salt spray corrosion testing 								
Features:	 Yellow Zinc coating exceeds 180/hr. salt spray resistance .0003 plating thickness Star Drive prevents cam out and stripping for improved driveability Type '17' reduces wood splitting and eliminates the need for pre-drilling Nibs under head provide flush finish Used in low corrosion applications 								
Coating:	The Zinc Yellow coating prevents the oxidation of steel by forming a protective barrier.								
Installation:	A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a T-25 Star drive bit. Do not over torque as it can cause the head to snap or damage to the work surface.								

Pullout Values (Avg. Lbs.)														
So. Yellow Pine		Douglas Fir		Chipboard		Plywood		Particle Board		Redwood				
Embedment	Lbs.	Embedment	Lbs.	Embedment	Lbs.	Embedment	Lbs.	Embedment	Lbs.	Embedment	Lbs.			
1-1/2"	1490	1-1/2"	1150	1"	370	3/4"	642	3/4"	425	3/4"	377			

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

¹(American Society of Testing Materials)

XT1031Y_XT1040Y_Rev. A (12/27/22)