

## GS 490 ECONOMY GRADE FIBERGLASS REINFORCED STRAPPING TAPE

### TYPICAL APPLICATIONS

- For light duty strapping, packaging, bundling and palletizing applications

### PRODUCT FEATURES

- Economy grade fiberglass reinforced strapping tape
- Good adhesion, quick stick and shock resistance
- Moisture- and solvent-resistant
- Will not split or crack

### CONSTRUCTION

Backing: Fiberglass reinforced, cast biaxially oriented polypropylene film

Adhesive: Synthetic rubber/resin hot melt adhesive

### STANDARD WIDTHS

0.47 in; 0.7 in; 0.94 in; 1.41 in; 1.88 in; 2.83 in  
12 mm; 18 mm; 24 mm; 36 mm; 48 mm; 72 mm

### STANDARD LENGTHS

60.1 yd, 328 yd  
55 m, 330 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

FDA Indirect Contact CFR 21, 175.105

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR



Clear  
(CLR)

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	70 oz/in width	7.66 N/10 mm
Elongation	3.70%	3.70%
Service Temperature Range	-10 F to 150 F	-23 C to 66 C
Tensile	100 lbs/in width	175.1 N/10 mm
Thickness	4.5 mils	0.11 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

