

Collated Exterior Screws



Deck-Drive™ DSV WOOD Screw

Preservative-Treated Decking and Exterior Wood-to-Wood Applications


The Deck-Drive DSV Wood screw is a powerful fastening solution for preservative-treated decking applications. With its underhead nibs and fast-start tip, the DSV is ideally suited to be driven and countersunk into today's wood deck boards. The shank is designed to withstand the swelling and shrinkage that is common with fast-growth lumber. Available in hand-drive and in collated strips for use in our Quik Drive® auto-feed screw driving system.

Features:

- Low-torque threads allow up to 35% more screws to be driven per battery charge
- Rimmed flat head with nibs design countersinks easily and provides a clean, finished appearance
- High-low threaded tip with Type-17 point provides fast starts
- Optimized threads for dimensional lumber
- Quik Guard® coating provides corrosion resistance for exterior and preservative-treated wood applications
- Meets the performance requirements of ICC-ES AC257 exposure conditions 1 and 3
- Colors to blend in with most woods
- This screw is also available in bulk for hand-drive installation; see p. 77 for details
- T25 6-lobe driver bit: BITTX25
- The #10 DSV are load rated; see C-F-2025TECHSUP references below

For Technical Data and Loads: see C-F-2025TECHSUP Fastening Systems Technical Guide, pp. 37–38, 50, 170–171, 192–193


Quik Guard Coating — Tan



Size	Length (in.)	500-Count Model No.	750-Count Model No.	1,000-Count Model No.	1,500-Count Model No.	2,000-Count Model No.	PRO 300SG2	PRO 250G2	PRO 200SG2	Project Pro™
# 8	1 ¼	—	—	—	—	DSVT114S			✓	
# 8	1 ½	—	—	HCKDSVT158S	—	DSVT158S		✓	✓	✓
#10	2	—	HCKDSVT2S	—	DSVT2S	—	✓	✓	✓	✓
#10	2 ½	HCKDSVT212S	—	DSVT212S	—	—	✓	✓		✓
#10	3	HCKDSVT3S	—	DSVT3S	—	—	✓			


 Tan


Quik Guard Coating — Red



Size	Length (in.)	1,000-Count Model No.	1,500-Count Model No.	2,000-Count Model No.	PRO 300SG2	PRO 250G2	PRO 200SG2	Project Pro
#8	1 ½	—	—	DSVR158S		✓	✓	✓
#10	2	—	DSVR2S	—	✓	✓	✓	✓
#10	2 ½	DSVR212S	—	—	✓	✓		✓
#10	3	DSVR3S	—	—	✓			


 Red

Quik Guard Coating — Gray



Size	Length (in.)	1,000-Count Model No.	PRO 300SG2	PRO 250G2	Project Pro
#10	2 ½	DSVG212S	✓	✓	✓
#10	3	DSVG3S	✓		


 Gray

Collated Exterior Screws



Deck-Drive™
DWP WOOD SS Screw


Decking, Docks and Boardwalks; Finishing, Millwork and Trim

The Deck-Drive DWP Wood SS screw is a powerful fastening solution for deck, dock and general exterior applications where extra corrosion protection is needed. With its specially-designed sharp-point and unique box threads, the DWP is ideally suited for the majority of wood used in today's wood deck boards. Choose Type 316 stainless steel for seaside and coastal environments. Available in hand-drive and in collated strips for use in our Quik Drive® auto-feed screw driving system.

Features:


- Unique “box” thread design with raised-ridge technology greatly reduces driving torque
- Specially-designed sharp point penetrates hard wood products with ease
- 6-lobe drive helps prevent driver-bit cam-out while driving easier and extending bit life (replacement bit: BITTX25; see p. 167 for more information)
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance
- This screw is also available in bulk for hand-drive installation; see pp. 74–76 for details
- Tested in accordance with ICC-ES acceptance criteria AC233 and load rated for withdrawal resistance

For Technical Data and Loads: see C-F-2025TECHSUP Fastening Systems Technical Guide, pp. 53–54, 169, 192–193



Type 316 Stainless Steel

Size	Length (in.)	1,000-Count Model No.	1,500-Count Model No.	PR0300SG2
#10	2½	—	SSDWP212S316	✓
#10	3	SSDWP3S316	—	✓



Type 305 Stainless Steel

Size	Length (in.)	1,000-Count Model No.	1,500-Count Model No.	PR0300SG2
#10	2½	—	SSDWP212S305	✓
#10	3	SSDWP3S305	—	✓

Collated Exterior Screws



Deck-Drive™
DHPD HARDWOOD Screw


Hardwood Decking, Docks and Boardwalks

The Deck-Drive DHPD Hardwood screw is specially designed to penetrate the hardest wood products with ease. With its unique paddle-style drill point, it virtually eliminates splitting without predrilling. The wings on the shaft counterbore hard material, allowing the head to countersink easily for a clean, finished look. Available in Type 305 stainless steel for additional corrosion protection.

Features:

- Penetrate the hardest wood products without predrilling
- Compact head ensures a low-profile installation and reduced visibility
- Wings on the shank counterbore hard material and allow the head to countersink for a clean look
- Driver bit included in each package
- #2 square drive (replacement bit: BIT2S; see p. 167 for more information)
- This screw is also available in bulk for hand-drive installation; see p. 78 for details

Type 305 Stainless Steel



Size	Length (in.)	Threads per Inch	Color	Contractor Pack		PRO300SG2
				Fasteners per Pack	Model No.	
#10	2½	10	Unpainted	1,000	SSDHPD212S	✓
#10	2½	10	Tan 03	1,000	SSDHPD212SB	✓




Tan 03

Trim-Head Screw — Sharp Point

Features:

- Trim head
- #2 square drive (driver bit in each box; replacement bit: BIT2S; see p. 167 for more information)
- Box threads
- Curved collation



Type 305 Stainless Steel

Size	Length (in.)	Head Color	Contractor Pack		PRO 250G2	PRO 300SG2
			Fasteners per Pack	Model No.		
#7	2	Unpainted	2,000	SSDTH2S	✓	
#7	2½	Unpainted	1,000	SSDTH212S	✓	
#7	3	Unpainted	1,000	SSDTH3S		✓
#7	2½	Brown 01	1,000	DTH212S305BR01	✓	
#7	2½	Brown 05	1,000	DTH212S305BR05	✓	
#7	2½	Gray	1,000	DTH212S305GR	✓	
#7	2½	Gray 01	1,000	DTH212S305GR01	✓	
#7	2½	Gray 03	1,000	DTH212S305GR03	✓	
#7	2½	Gray 04	1,000	DTH212S305GR04	✓	
#7	2½	Tan	1,000	DTH212S305TN	✓	
#7	2½	Tan 01	1,000	DTH212S305TN01	✓	
#7	2½	Tan 02	1,000	DTH212S305TN02	✓	
#7	2½	Tan 03	1,000	DTH212S305TN03	✓	
#7	2½	Tan 04	1,000	DTH212S305TN04	✓	
#7	2½	Red 01	1,000	DTH212S305RD01	✓	



Collated Exterior Screws




Trim-Head Screw — Type-17 Point

Features:

- Trim head with nibs for easy countersinking
- #2 undersized square drive (driver bit in each box; replacement bit: BIT2SU; see p. 167 for more information)
- Coarse threads
- Curved collation

Quik Guard® Coating



Size	Length (in.)	Contractor Pack		PR0200SG2	PR0250G2	PR0300SG2
		Fasteners per Pack	Model No.			
#8	2	2,000	DTHQ2S	✓	✓	✓
#8	2½	1,500	DTHQ212S		✓	✓
#8	3	1,000	DTHQ3S			✓


Bugle-Head Wood Screw

Common Applications:

- Wood decking to wood


Features:

- #3 square drive (driver bit in each box; replacement bit: BIT3S; see p. 167 for more information)
- Coarse threads
- Type-17 point for fast starts
- Available in Types 316 and 305 stainless steel
- Curved collation



Type 316 Stainless Steel

Size	Length (in.)	Carton Quantity	Model No.	PR0300SG2
#10	2½	1,500	SS3DSC212BS316	✓
#10	3	1,000	SS3DSC3BS316	✓



Type 305 Stainless Steel

Size	Length (in.)	Carton Quantity	Model No.	PR0300SG2
#10	2½	1,500	SS3DSC212BS	✓
#10	3	1,000	SS3DSC3BS	✓

CB3BLG Fiber-Cement Board Screw


Common Applications:

- Dense fiber-cement board to wood

Features:

- 0.375" ribbed wafer head with nibs for easy countersinking
 - #3 undersized square drive (driver bit in each box; replacement bit: BIT3SU; see p. 167 for more information)
- Coarse threads
 - Type-17 point for fast starts
 - C-3 mechanically galvanized coating
 - Straight collation

Codes/Standards: ANSI A108 compliant



C-3 Mechanically Galvanized Coating

Size	Length (in.)	Threads per Inch	Contractor Pack		PROLDHG2
			Fasteners per Pack	Model No.	
#10	1 1/4	10	1,500	CB3BLG114S	✓
#10	1 5/8	10	1,500	CB3BLG158S	✓

CB3BLGHL Cement Board Screw


Common Applications:

- Cement board to wood (for coarse, porous and softer materials)

Features:

- 0.375" ribbed wafer head with nibs for easy countersinking
 - #3 undersized square drive (driver bit in each box; replacement bit model BIT3SU; see p. 167 for more information)
- Alternating high-low threads
 - Sharp point
 - C-3 mechanically galvanized coating
 - Straight collation


Codes/Standards: ANSI A108 compliant



C-3 Mechanically Galvanized Coating

Size	Length (in.)	Threads per Inch	Contractor Pack		PROLDHG2
			Fasteners per Pack	Model No.	
#9	1 1/4	15 high-low	1,500	CB3BLGHL114S	✓
#9	1 5/8	15 high-low	1,500	CB3BLGHL158S	✓

Collated Exterior Screws



SSWSCB Roofing Tile Screw

Common Applications:


- Roofing tiles to wood

Features:

- Bugle head
- Coarse threads
- #2 square drive (driver bit in each box; replacement bit: BIT2S; see p. 167 for more information)
- Type-17 point for fast starts
- Curved collation

Codes/Standards: Meets the requirements of the Tile Roofing Institute as described in ESR-2015P. A Miami-Dade compliant roofing product (2" and 2½" only). Miami-Dade Fastener Listing 18-1218.01.

Type 305 Stainless Steel



Size	Length (in.)	Carton Quantity	Model No.	PR0RFG2	PR0300SRFG2
#8	1¾	2,000	SSWSC134BS	✓	
#8	2	2,000	SSWSC2BS	✓	✓
#8	2½	1,500	SSWSC212BS	✓	✓

Collated Exterior Screws



WSCT Roofing Tile Screw


Common Applications:

- Roofing tiles to wood

Features:

- Flat head
- #3 square drive (driver bit in each box; replacement bit: BIT3S; see p. 167 for more information)
- Twin threads
- Sharp point
- Curved collation

Codes/Standards: ASTM A641 (Class 1)



Heavy Zinc Electroplate

Size	Length (in.)	Carton Quantity	Model No.	PR0RFG2	PR0300SRFG2
#8	2½	1,500	WSCT212S	✓	✓

WSTD Roofing Tile Screw


Common Applications:

- Roofing tiles to wood

Features:

- Flat head
- #3 square drive (driver bit in each box; replacement bit model BIT3SU; see p. 167 for more information)
- Twin threads
- Sharp point
- Curved collation

Codes/Standards: Meets the requirements of the Tile Roofing Institute as described in ESR-2015P. A Miami-Dade compliant roofing product. Miami-Dade Fastener Listing 21-1202.01.



Exterior-Grade Coating

Size	Length (in.)	Carton Quantity	Model No.	PR0RFG2	PR0300SRFG2
#8	2½	1,500	WSTD212S	✓	✓
#8	3	1,500	WSTD3S		✓